

Small in size
and low in
cost - rich in
optional
features



FUJITSU Server PRIMERGY RX1330 M4

한국후지쯔 PRIMERGY RX1330 M4 모델은 비용 효율적인 서버입니다.

Intel Xeon E-2100 v6 CPU와 DDR4 2666 MHz 메모리가 탑재된 본 제품은 3.5" 하드디스크 4개, 혹은 2.5" 10개를 탑재가 가능하고, 최대 3개의 IO Slot 제공으로 높은 확장성을 자랑합니다.

또한, 서버 내부 배터리인 FUJITSU FJBU (Internal UPS)의 지원으로, 높은 에너지 효율과 안정적인 전원공급을 자랑합니다.

PRIMERGY RX1330 M4은 1U 크기로 공간 효율성을 극대화하여 다양한 IT 환경에 적합한 제품입니다.

- 최대 4코어의 Intel® Xeon® E3 v6 프로세서 제품군 탑재
- 4개의 3.5" SAS/SATA, 또는 10개의 2.5" SAS/SATA 하드디스크 탑재 가능
- Microsoft Windows Server / VMware / SUSE / RedHat OS 지원
- Fujitsu ServerView™ suite 및 onboard 원격관리칩셋 (iRMC S5)을 통한 중앙관리기능 무상 제공
- 최대 40°C의 온도에서 정상 동작 가능한 Cool-safe® Advanced Thermal Designa



shaping tomorrow with you

FUJITSU

TECHNICAL DETAILS

PRIMERGY RX1330 M4

Chipset	Intel® C246
Processor	Intel® Xeon® processor E-2186G (6C/12T, 3.80 GHz, up to 4.3 GHz, 2,666 MHz) Intel® Xeon® processor E-2176G (6C/12T, 3.70 GHz, up to 4.3 GHz, 2,666 MHz) Intel® Xeon® processor E-2174G (4C/8T, 3.80 GHz, up to 4.3 GHz, 2,666 MHz) Intel® Xeon® processor E-2146G (6C/12T, 3.50 GHz, up to 4.2 GHz, 2,666 MHz) Intel® Xeon® processor E-2144G (4C/8T, 3.60 GHz, up to 4.2 GHz, 2,666 MHz) Intel® Xeon® processor E-2136 (6C/12T, 3.30 GHz, up to 4.2 GHz, 2,666 MHz) Intel® Xeon® processor E-2134 (4C/8T, 3.50 GHz, up to 4.2 GHz, 2,666 MHz) Intel® Xeon® processor E-2126G (6C/6T, 3.30 GHz, up to 4.1 GHz, 2,666 MHz) Intel® Xeon® processor E-2124G (4C/4T, 3.40 GHz, up to 4.1 GHz, 2,666 MHz) Intel® Xeon® processor E-2124 (4C/4T, 3.30 GHz, up to 3.9 GHz, 2,666 MHz) Intel® Pentium® processor G5400 (2C/4T, 3.70 GHz, 2,666 MHz) Intel® Core™ i3-8100 processor (4C/4T, 3.60 GHz, 2,400 MHz) Intel® Celeron® processor G4900 (2C/2T, 3.10 GHz, 2,400 MHz)
Memory	8 GB - 64 GB, 4 DIMMs (DDR4, 2 banks with 2 DIMMs each), ECC protection
Drive bays (Base unit specific)	4x 3.5-inch hot-plug SAS/SATA 8x 2.5-inch hot-plug SAS/SATA 10x 2.5-inch hot-plug SAS/SATA (limitations : No CD-RW/DVD, 1x USB at the front, no front VGA)
Storage disks	HDD SATA, 6 Gb/s, 500 GB/1 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, economic HDD SATA, 6 Gb/s, 1 TB/2 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical HDD SATA, 6 Gb/s, 1 TB/2 TB/4TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical HDD SATA, 6 Gb/s, 6 TB/12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical HDD SAS, 12 Gb/s, 300 GB/600 GB/900 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise HDD SAS, 12 Gb/s, 600 GB/900 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise HDD SAS, 12 Gb/s, 6 TB/12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED HDD SAS, 12 Gb/s, 1.2 TB/1.8 TB/2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise SSD SATA, 6 Gb/s, 240 GB/480 GB/ 960 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 0.9 DWPD SSD SATA, 6 Gb/s, 240 GB/480 GB/960 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD SSD SATA, 6 Gb/s, 1.92 TB/3.84 TB/7.68 TB, Read-Intensive, hot-plug, 2.5-inch/3.5-inch, enterprise, 0.5 DWPD SSD SATA, 6 Gb/s, 1.92 TB/3.84 TB, Mixed-use, hot-plug, 2.5-inch/3.5-inch, enterprise, 3 DWPD SSD M.2 SATA, 6 Gb/s, 240 GB/480 GB, non hot plug, enterprise, 1.4 DWPD
Optical & Tape Drives	Blu-ray Disc™ Triple Writer, (6x BD-RW, 8x DVD, 24x CD), ultraslim, SATA I DVD Super Multi ultra slim, (8x DVD; 24x CD), ultraslim, SATA I
Graphics	NVIDIA® Quadro® P400, 2 GB, PCIe x16, 3x miniDP
Interfaces and Slots	2 Rear: 2x USB 2.0 (10x 2.5" HDD base unit: 1x USB 2.0) 4 Total, Front: 2x 3.1 Gen1 Type A, Rear: 2x 3.1 Gen2 Type A (10x 2.5" HDD base unit: 4x rear USB 3.0) 1 x VGA (15-pin) / optional 1 x front VGA (not for 10x 2.5" HDD base unit) 1 x serial RS-232-C Optional 2 x 1 Gbit/s Ethernet Management LAN traffic can be switched to shared onboard Gbit LAN port 1 x dedicated management LAN port for iRMC S5 (10/100/1000 Mbit/s) PCI-Express 3.0 x4, 1 x Low profile PCI-Express 3.0 x8, 2 x Low profile Length 175mm; PCIe slot#1 supports Modular RAID functions
Dimensions / Electrical values	482.6 mm (Bezel) / 435.4mm (Body) x 572 mm x 42.8 mm, 1U, up to 13 kg 300/450 W (92% / 94% efficiency : 80 plus "Gold" / "Platinum") Operating condition 5 - 45°C, 10 - 85 % (non condensing) by Cool-Safe™ Advanced Thermal Design Compliance link: http://globalsp.ts.fujitsu.com/sites/certificates
Operating Systems and Virtualization Software	Microsoft® Hyper-V Server 2016 Microsoft® Windows Server® 2016 Essentials / Standard / Datacenter Microsoft® Windows Server® 2019 Essentials / Standard / Datacenter Windows Storage Server 2016 Standard Windows Server Datacenter, version 1709 VMware vSphere™ 6.5 VMware vSphere™ 6.7 SUSE® Linux Enterprise Server 12 Red Hat® Enterprise Linux 7

* Note: Support of other Linux derivatives on demand

한국후지쯔 (주)
<http://www.fujitsu.com/kr/>

서울특별시 종로구 종로1 (교보생명 빌딩)
전화: (02)3787-6000 / 팩스: (02)738-1079
고객지원센터 FQRC 전화: (080)750-6000